


- Highly moisture resistant
- FSC®-certified particleboard
- NAF-no added formaldehyde
- 100% post-industrial recycled/recovered content
- Declare Product
- High pine content
- CARB Exempt
- EPA TSCA Title VI Compliant







Collins Pine FreeForm® MR50 Particleboard

CollinsWood.com

MR50 panel is FSC®-certified, NAF, CARB Exempt, contains 100% post-industrial/pre-consumer recycled & recovered fibers, and is the first MR50 rated particleboard on the market.



- Consistent light tan color—best for thin papers and melamines
- No thin edges—panels sawn after sanding
- EPA TSCA Title VI Compliant



SCS Validation SCS-NAF-04354



Physical Properties

Density	49 lbs/cu ft
Internal Bond	150 psi
Modulus of Rupture	2,500 psi
Modulus of Elasticity	410,000 psi
Screw Holding - Face	300 lbs
Screw Holding - Edge	240 lbs

Sizes/Thickness

Press Size	5' x 24'	
Thickness	5/8" to 1-1/8"	
Thickness Tolerance	$\pm .003$ " average thickness from target	
L/W Tolerance	± 1/16"	
Squareness Tolerance	± 1/32" per foot of panel width	

Physical properties tested using method ASTM D 1037-06a. Complies and meets the moisture resistance characteristics defined by ANSI A208.1-2022.

Collins Pine FreeForm® MR50 Particleboard passes the stringent MR50 criteria for both thickness swell and advanced aging/degradation.

Our NAF resin enables our products to be third-party certified CARB Exempt TSCA Title VI.

INFORMATION & SALES

Mike Shuey

mshuey@collinsco.com 503.826.5222

Toll Free: 800.547.1793

COLLINSWOOD® FSC

Made in Klamath Falls, Oregon USA

- Hardwood Lumber
- Softwood Lumber
- Collins Pine Particleboard
- Collins Pine FreeForm® Particleboard
- TruWood® Siding Trim

