

# **Industrial 2**

NAF-NO ADDED FORMALDEHYDE

**MOISTURE RESISTANT / MEETS ANSI MR10** 

100% POST-INDUSTRIAL RECYCLED/RECOVERED CONTENT

HIGH PINE CONTENT

**CARB EXEMPT** 

**EPA TSCA TITLE VI COMPLIANT** 







Industrial 2 meets ANSI MR10 rating, is NAF, CARB Exempt, contains 100% post-industrial/pre-consumer recycled & recovered fibers, and is available FSC®-certified.

- Excellent machinability—extends tool life
- Consistent light tan color—best for thin papers and melamines
- No thin edges—panels sawn after sanding
- EPA TSCA Title VI Compliant



**SCS Validation** SCS-NAF-04354



#### **Physical Properties**

Density	46 lbs/cu ft	
Internal Bond	90 psi	
Modulus of Rupture	1,900 psi	
Modulus of Elasticity	320,000 psi	
Screw Holding - Face	225 lbs	
Screw Holding - Edge	180 lbs	

### Sizes/Thickness

Press Size	5' x 24'
Thickness	5/8" to 1-1/8"
Thickness Tolerance	±.003" average thickness from target
L/W Tolerance	1/16"
Squareness Tolerance	1/32" per foot of panel width

Physical properties tested using method ASTM D 1037-06a. Complies and meets the moisture resistance characteristics defined by ANSI A208.1-2022.

Collins Pine Particleboard Industrial 2 passes the stringent MR10 criteria for reducing thickness swell.

Our NAF resin enables our products to be third-party certified CARB Exempt TSCA Title VI.

#### **INFORMATION & SALES**

#### Steve Stoler

sstoler@collinsco.com 503.826.5222

## Dominic Mattos Jr. LEED GA

dmattos@collinsco.com 503.793.1130

Toll Free: 800.547.1793

Manufactured at: 6410 Highway 66 Klamath Falls, OR 97601

#### COLLINSWOOD® FSC

Hardwood Lumber

Softwood Lumber

- Collins Pine FreeForm<sup>®</sup>
- Collins Pine Particleboard
- Collins Pine FreeForm® MR50





Made in Klamath Falls, Oregon USA